SRC LOW LEVEL LIFTER/DUMPER FOR REMOVABLE MIXING BOWLS



PROFESSIONAL

MODEL


■ SRC1 ■ SRC2

SRC1: for bowls with maximum capacity up to 300 Kg SRC2: for bowls with maximum capacity up to 550 Kg





TECHNICAL FEATURES



TECHNICAL DATA MODEL			SRC1					SRC2	
			C 130	C 160	C 200	C 250	C 300	C 400	C 500
Motor power kw			0,75	0,75	0,75	0,75	0,75	1.1	1.1
Current drawn V 230/400 A		3/1.8	3/1.8	3/1.8	3/1.8	3/1.8	5/2.8	5/2.8	
Height from bowl edge during discharging phase	Н	mm	1260	1260	1260	1260	1260	1280	1280
Total height of trolley during discharging phase	ΗT	mm	2540	2640	2640	2790	2890	3000	3100
Total width	L	mm	1100	1100	1100	1100	1100	1200	1200
Depth	Ρ	mm	1420	1420	1420	1420	1420	1470	1470
Total depth	PT	mm	1630	1730	1730	1850	1960	2050	2150
Lifting capacity kg		800	800	800	800	800	1000	1000	
Net weight		kg	370	370	370	370	370	420	420

All data are to be considered as nominal, MIXER srl reserves the right to make any changes to the product and/or technical specifications without notice.

STANDARD FEATURES

- Electric controls on both sides with hold-on-to run buttons.
- Frontal dumping.

- Painted stainless steel structure raised from the ground by 4 adjustable feet.
- Lifter/dumper with hydraulic system (dumping height 130 cm).

ON REQUEST

- Stainless steel structure with micro shot-peening treatment.
- Special construction to discharge at 500 mm height.

- Special connection for bowl not manufactured by MIXER.
- Packaging in wooden crate.

Note: for bowl-trolleys connections not produced by our company, it is necessary to have the bowl to be dumped available at our premises for at least one week. This allows us performing the necessary activities and guaranteeing the correct operation.

